Frequently Asked Questions:

What's wrong with conventional earplugs?

A They muffle speech and music. Conventional earplugs reduce sound more in the high frequencies than in the low and mid frequencies, which makes music and voices *unclear* and unnatural. Deeply-inserted foam earplugs can provide 30-40 dB of sound reduction, but only a small amount is typically needed.

How much protection do people need?

A Hearing loss is a function of exposure time, the average sound level, and the peak level of very loud sounds. Some persons are more susceptible to hearing loss from high-level sound than others. Most musicians do not need maximum protection, and many industrial workers can be adequately protected with as little as 10 dB of sound reduction. The majority of eight-hour-equivalent noise exposure in industry falls between 85 and 95 dB.

Is there a non-custom high fidelity earplug?

A Yes. Etymotic Research designed and patented ETY•Plugs**

which are high fidelity ready-fit earplugs that reduce sound evenly by 20 dB at all frequencies, so that music and speech are heard clearly. Available in two sizes, for regular and small ear canals.



Regular Small

Why are deep earmolds required for Musicians Earplugs?

A Earmolds need to seal deeply in the bony portion of the ear canal or the wearer will hear a hollow or boomy sound in their own voice when speaking, singing or playing a brass or wind instrument. This unpleasant or distracting sound is called the *occlusion effect*. Deep earmolds (past the second bend of the ear canal) will eliminate this problem.

What is the noise reduction rating (NRR)?

The U.S. Environmental Protection Agency requires manufacturers to print a noise reduction rating (NRR) on all non-custom earplugs. The formula used to determine NRR includes an adjustment for test variability, individual variability, and for those persons who do not wear ear protection as instructed. When worn properly, Etymotic earplugs provide more sound reduction than the assigned NRR value. Laboratory data on subjects wearing properly sealed *ETY•Plugs*™ shows between 18-22 dB average sound reduction over the 250-8000 Hz frequency range, but the NRR calculated from the same data is 12 dB.

Who uses Musicians Earplugs?

Aircraft

flight instructors passengers pilots

Athletics

athletes coaches sporting events

Construction

carpenters
equipment operators
road builders
steel workers

Emergency Vehicles

EMTs highway patrol firefighters

Industrial

factory workers shop teachers students supervisors

Leisure

concerts night clubs noisy restaurants

Medical-Dental

dental hygienists dental technicians surgeons

Motor Sports motorcyclists

pit crews race car drivers spectators

Music


concerts marching bands musicians night clubs

Others

delivery drivers market traders night club staff truck drivers



Permissible Sound Exposure Guidelines



peak level of very loud sounds.

NIOSH (1998). Criteria for a recommended standard: occupational noise exposure. Cincinnati, OH: U.S. Department of Health and Human Services, Public Health Service, Centers for Disease Control and Prevention, and National Institute for Occupational Safety and Health. DHRs (MIOSH) Publication No. 98-126.

Musicians Earplugs

FR-9 • FR-15 • FR-25



- Custom high-fidelity hearing protection
- Sound quality is clear and natural, not muffled
- Noise fatigue and ear overload distortion are reduced

ETYMŌTIC RESEARCH INC.

61 Martin Lane • Elk Grove Village, IL 60007
www.etvmotic.com • 888-389-6684


Musicians Earplugs $^{\mathrm{IM}}$ is a trademark of Etymotic Research, Inc. The ER family of earplugs is covered by one or more of the following U.S. patents: \pm 4,852,683, \pm 5,113,967, \pm 5,887,070 and other patents pending.

eatents pending. EREM-B01-B 0907



What Makes Musicians Earplugs High Fidelity?

Musicians Earplugs™ replicate the natural response of the ear canal so that sound heard with these earplugs has the same quality as the original, just quieter.



ER-15 Musician Earplugs provide 15 dB sound reduction at each frequency.

fidelity

3. exact

/fidélitee/ n.

1. faithfulness:

loyalty. **2.** strict conformity to truth or fact.


correspondence

to the original

4. precision in

reproduction of

sound or video



Average sound reduction of Musicians Earplugs and foam earplugs.

Permissible Sound Exposure Guidelines


Continuous Sound dBA	Unprotected Permissible Exposure Time
85	8 hours
88	4 hours
91	2 hours
94	1 hour
97	30 minutes
100	15 minutes
103	7.5 minutes
106	< 4 minutes
109	< 2 minutes
112	~1 minutes
115	~30 seconds

About Musician Earplugs

Musicians Earplugs were designed to protect hearing while preserving all the subtleties and richness of music. Other earplugs, particularly foam, muffle sound so music and speech are not heard distinctly. Musicians Earplugs are made from custom ear impressions and tested to ensure that sound heard with them is accurate and true—the definition of high fidelity. Music and speech reproduced through these earplugs sounds exactly as it would in an ear without an earplug, but at a lower (safer) loudness level.

Musicians practice and perform in a variety of different settings and they are exposed to high levels of sound, sometimes for long periods. They require different amounts of hearing protection depending on the sound levels they encounter during rehearsals and performances. See the table to the right.

Which Earplug is Best for You?



Ref: Chasin, M. Musicians and the Prevention of Hearing Loss. Singular Publishing Group. 1996

Quick Reference Guide

Three types of attenuator buttons are available: ER-9, ER-15, and ER-25. The number corresponds with the amount of sound reduction provided in dB.

Description

Button Colors

Interchangability

Earmold styles

Insertion

Cleaning

Replacement



ER-9 Musicians Earplug ER-15 Musicians Earplug ER-25 Musicians Earplug Flat 9 dB sound reduction through Provides uniform 15 dB sound Provides 25 dB of relatively flat the mid range. Same high reduction across all frequencies sound reduction across frequency protection as the ER-15 all frequencies Clear Blue Identical dimensions. Change buttons for different listening conditions. Standard Partially countersunk Countersunk Moisten the mold for ease of insertion. Pull the ear outward and upward while easing the mold into the ear canal. Remove button from mold. Use water and mild soap on the mold only. Dry mold thoroughly before replacing button. Discoloration, shrinkage, cracking, hardening of earmold material, deterioration in performance.

Musicians Earplugs require custom earmolds. Deep impressions past the second bend of the ear canal must be taken to ensure the effectiveness of these earplugs and to reduce the occlusion effect.

NIOSH (1998)